



Specification:

Model	UPG 2500E
Frequency (HZ)	50
Rated Output (KVA)	1.8
Maximum Output (KVA)	2.0
Rated Voltage (V)	220
Rated current (A)	8.2
Rated rotation speed (rpm)	3000
Phase No.	Single phase
Power Factor	1.0
Excitation Mode	Self-excitation, 2 pole and constant voltage (AVR)
DC Output	12V./8.3A ,Terminal Post
Noise Level (7m) dB(A)	77
Engine Model	KM170FE
Engine type	Single-Cylinder, Vertical, Four-Stroke, Direct Injection,Air Cooled Diesel
Bore × Stroke(mm)	70 x 55
Displacement (L)	0.211
Rated Power KW	2.5/3000
Fuel consumption Rate (g.kw/h)	280.2
Compression Ratio	20:1
Lubrication System	Pressure Splashed
Starting System	Electric Start with 30Ah MF battery
Fuel Type	0#(summer)-10#(winter) diesel
Lube Oil Brand	SAE10W30 (above CD Grade)
Lube Capacity (L)	0.75
Fuel Tank Capacity (L)	12.5
Continuous Running Time (hr)	20
Overall Dimension: LxWxH (mm)	660 x 500 x 570
Dry Weight (Kg)	60
Quantity in 20FT	132 PCS
Optional Features: Remote,ATS(Auto Transfer Switch) ,Digital Panel	
We reserve the right to change specifications without notice	